

GRAFTON

- 8" x 8" • Satin finish • In Stock
- Walls, floors, backsplashes, showers
- Residential, light commercial

Abbey Blue



Abbey Taupe



Pearl White



Dorset Taupe



Dorset Blue



Capel Blue




Capel Taupe



In stock

Images are for reference only; please refer to live product for an accurate color representation.

GRAFTON



In stock

Images are for reference only; please refer to live product for an accurate color representation.

ROBERT E. HENRY
TILE COMPANY
EST. 1933

GRAFTON



In stock

Images are for reference only; please refer to live product for an accurate color representation.

ROBERT E. HENRY
TILE COMPANY
EST. 1933

GRAFTON

SERIE GRAFTON - GRAFTON COLLECTION - COLLECTION GRAFTON

Baldosas cerámicas prensadas en seco Grupo B1a ($E_b \leq 0,5\%$), para suelos y paredes, exteriores e interiores. EN 14411, Anexo G, GL.

Dry-pressed ceramic tiles Group B1a ($E_b \leq 0,5\%$), for internal and external walls and floorings. EN 14411, Annex G, GL.

Carreaux céramiques pressés à sec Groupe B1a ($E_b \leq 0,5\%$), pour sols et murs, extérieurs et intérieurs. EN 14411, Annexe G, GL.

Características <i>Features</i> Caracteristiques	Norma de ensayo <i>Test standard</i> Norme d'essai	Valor <i>Value</i> Valeur
Características dimensionales <i>Dimensional features</i> Caractéristiques dimensionnelles	EN-ISO-10545-2	Cumple <i>Accomplish</i> Conforme
Absorción de agua <i>Water absorption</i> Absorption d'eau.	EN-ISO-10545-3	$\leq 0,5\%$
Resistencia a la flexión <i>Bending strength</i> Résistance à la flexion Fuerza de rotura <i>Breaking strength</i> Force de rupture	EN-ISO-10545-4	$\geq 35 \text{ N/mm}^2$ $\geq 1300 \text{ N}$
Resistencia a la abrasión <i>Resistance to surface abrasion</i> Résistance à l'abrasion	EN-ISO-10545-7	Clase 5 <i>Class 5</i> Classe 5
Resistencia al choque térmico <i>Thermal shock resistance</i> Résistance aux chocs thermiques	EN-ISO-10545-9	Cumple <i>Accomplish</i> Conforme
Resistencia al cuarteo <i>Crazing resistance</i> Résistance au craquelage	EN-ISO-10545-11	Cumple <i>Accomplish</i> Conforme
Resistencia a la helada <i>Frost resistance</i> Résistance au gel	EN-ISO-10545-12	Cumple <i>Accomplish</i> Conforme
Resistencia química <i>Chemical resistance</i> Résistance aux produits chimiques	EN-ISO-10545-13	GHA
Resistencia a las manchas <i>Resistance to stains</i> Résistance aux tâches	EN-ISO-10545-14	5
Deslizamiento <i>Friction coefficient</i> Péndulo <i>Pendulum</i> Pendule Rampa <i>Inclined Platform</i> Rampe DCOF <i>DCOF</i> DCOF	UNE-ENV-12633 DIN 51130 ANSI A137.1	C1 R9 >0.42
Resistencia al fuego <i>Resistance to fire</i> Résistance au feu	UNE-EN-13501-1	A1-A1 _{FL}

In stock

Images are for reference only; please refer to live product for an accurate color representation.

ROBERT E. HENRY
TILE COMPANY
EST. 1933